

Specification Sheet

Part Number: PR1M4



Panel Rivet, PA66, Natural, 1000/bag

Article Number

181-00139

Type

PR1

Color

Natural (NA)

Features & Benefits

- Panel rivets are made with nylon material to hold duct securely to the panel without corroding, ensuring longevity.
- Panel rivets can be easily inserted with use of a specially designed, long shafted panel rivet tool.
- Ergonomic design of the tool ensures effortless use when inserting rivets into deep channels or locations difficult to access.

Quantity Per

EA

Product Description

HellermannTyton panel rivets are one piece drive rivets that provide a fast, economic means of affixing wiring duct. The rivet is inserted into a 3/16" pre-punched hole and the pin is driven into the base, thereby expanding the rivet legs and locking the duct and sub-panel in place. The panel thickness (including the duct thickness) should be a maximum of 3/16".

Short Description	Panel Rivet, PA66, Natural, 1000/bag
Global Part Name	PR1-PA66-NA
Technical Description	Panel Rivet
Minimum Tensile Strength (Imperial)	107.0
Minimum Tensile Strength (Metric)	478
Panel Thickness Min(Imperial)	0.15
Panel Thickness Max(Imperial)	0.28
Panel Thickness Min (Metric)	3.9
Panel Thickness Max (Metric)	7.0
Mounting Hole Diameter D (Imperial)	0.2
Mounting Hole Diameter D (Metric)	5.0 mm
Mounting Hole Diameter D Max (Metric)	5.0
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 HB

Halogen free Yes

Operating Temperature (Metric) -40°F to +176°F (-40°C to +80°C)

Reach Complaint(Article 33) No

ROHS Complaint Yes

Package Quantity(Imperial) 1000

Package Quantity (Metric) 1000

Customs Number 3925900000