


JKL PART NUMBER	COLOR RGB HIGH OUTPUT WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF4418-20B	5600° KELVIN	1,400 @ 0°C	650	5 ± 1	15,000±10%	20,000

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION TITLE SINGLE LEAD TIPLESS MINIATURE FLUORESCENT LAMP						
		DRAWN BY L. WENGSTROM		APPVD BY DATE LARRY R. 8/14/07		SIZE A	FSCM NO. 55335	DRAWING NO. BF4418-20B				
REV. NO.		DESCRIPTION/ECO NUMBER		APPVD DATE		SCALE NONE	RELEASED DATE 8/14/07		REVISION DATE	REV. NO.	SHEET 1 OF 1	
RELEASED TO CAD		8/14/07		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED								