

Specification Sheet

Part Number: CTT60R0HIRHSM4



Clamp Tie, 8" Long, 60lb Tensile Strength, PA66HIRHS, Black, 1000/pkg

Article Number	112-52111
Type	CTT60R
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• High impact and heat stabilized cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.• Head design contains clamping rails to provide full circumferential compression around bundles.• Bent tail allows for quick insertion into head.
Quantity Per	bag

Product Description

The 360 Degree compression ties were designed with underside clamping rails to allow for optimal surface contact and complete circumferential compression around the bundle. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description	Clamp Tie, 8" Long, 60lb Tensile Strength, PA66HIRHS, Black, 1000/pkg
Global Part Name	CTT60R-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	60.0
Minimum Tensile Strength (Metric)	265.0
Length L (Imperial)	8.0
Length L (Metric)	205.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.19
Width W (Metric)	4.7
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.8
Bundle Diameter Max (Metric)	45.0
Thickness T (Metric)	1.2

Material	Polyamide 6.6 high impact modified, heat and UV-resistant (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909987
Weight (Metric)	0.0012
Weight (Imperial)	0.0027